





| 共通规格 |                                 |
|------|---------------------------------|
| 精度等级 | JIS N8级 (JIS B 1702-1 : 1998) * |
| 齿形   | 全齿高齿                            |
| 压力角  | 20°                             |
| 材料   | 快削黄铜 (C3604)                    |
| 热处理  | —                               |
| 齿面硬度 | (80HV 以上)                       |


\*模数 0.8 以下的产品精度是与表记精度相当的产品。



S3T



S1



S1T

| 产品型号       | 模数   | 齿数   | 形状  | 孔径              | 轮毂径  | 分度圆直径 | 齿顶圆直径 | 齿宽 | 轮毂长 | 全长 | 键槽<br>宽度×深度 |    |   |    |
|------------|------|------|-----|-----------------|------|-------|-------|----|-----|----|-------------|----|---|----|
|            |      |      |     | A <sub>H7</sub> | B    | C     | D     | E  | F   | G  |             |    |   |    |
| BSS0.5-15A | m0.5 | 15   | S3T | 3               | 8.5  | 7.5   | 8.5   | 3  | 11  | 14 | —           |    |   |    |
| BSS0.5-16A |      | 9    |     |                 | 8    | 9     | 7     |    | 10  |    |             |    |   |    |
| BSS0.5-20  |      | 20   | S1  | 4               | 8.5  | 10    | 11    | 7  | 10  |    |             |    |   |    |
| BSS0.5-20A |      | 3    |     | 11              | 11   | 14    |       |    |     |    |             |    |   |    |
| BSS0.5-22A |      | 22   | S1T | 3               | 9    | 11    | 12    | 7  | 10  |    |             |    |   |    |
| BSS0.5-24B |      | 4    |     | 10              | 12   | 13    |       |    |     |    |             |    |   |    |
| BSS0.5-25  |      | 25   | S1  | 4               | 11   | 12.5  | 13.5  | 11 | 14  |    |             |    |   |    |
| BSS0.5-30  |      | 30   | S1  | 4               | 13   | 15    | 16    | 7  | 10  |    |             |    |   |    |
| BSS0.5-30A |      |      |     | 3               | 12   |       |       |    |     |    |             |    |   |    |
| BSS0.5-30B |      |      |     | 4               | 12   |       |       |    |     |    |             |    |   |    |
| BSS0.5-30C |      |      |     | 5               | 12   |       |       |    |     |    |             |    |   |    |
| BSS0.5-38A |      | 38   | S1T | 4               | 16   | 19    | 20    | 4  | 8   | 12 |             |    |   |    |
| BSS0.5-40  |      | 40   | S1  | 4               | 17   | 20    | 21    |    |     |    |             |    |   |    |
| BSS0.5-50A |      | 50   | S1T | 4               | 22   | 25    | 26    |    |     |    |             |    |   |    |
| BSS0.8-20  |      | m0.8 | S1  | 5               | 13.5 | 16    | 17.6  |    |     |    |             | 4  | 8 | 12 |
| BSS0.8-24B |      |      |     |                 | 16   | 19.2  | 20.8  |    |     |    |             |    |   |    |
| BSS0.8-25  | 17   |      |     |                 | 20   | 21.6  |       |    |     |    |             |    |   |    |
| BSS0.8-30  | S1   |      | 5   | 20              | 24   | 25.6  |       |    |     |    |             |    |   |    |
| BSS0.8-30A |      |      | 4   | 20              | 32   | 33.6  |       |    |     |    |             |    |   |    |
| BSS1-16B   | m1   | S1T  | 6   | 5               | 12   | 18    | 6     |    |     |    | 8           | 14 |   |    |
| BSS1-18B   |      |      |     | 6               | 15   | 20    |       |    |     |    |             |    |   |    |
| BSS1-20C   |      |      |     | 6               | 16   | 22    |       |    |     |    |             |    |   |    |
| BSS1-30B   |      |      |     | 6               | 25   | 32    |       |    |     |    |             |    |   |    |
| BSS1-40A   |      |      |     | 6               | 28   | 42    |       |    |     |    |             |    |   |    |

| 螺孔 |     | 容许转矩 (N·m) |              | 侧隙<br>(mm) | 质量<br>(kg) | 产品型号       |
|----|-----|------------|--------------|------------|------------|------------|
| 尺寸 | J   | 弯曲强度       | 容许转矩 (kgf·m) |            |            |            |
| M3 | 2.5 | 0.058      | 0.0059       | 0~0.10     | 0.0054     | BSS0.5-15A |
|    |     | 0.065      | 0.0066       |            | 0.0062     | BSS0.5-16A |
| —  | —   | 0.091      | 0.0093       |            | 0.0043     | BSS0.5-20  |
| M3 | 2.5 | 0.10       | 0.011        |            | 0.0098     | BSS0.5-20A |
|    |     |            |              |            | 0.0054     | BSS0.5-22A |
| M3 | 3.5 | 0.12       | 0.012        |            | 0.0063     | BSS0.5-24B |
|    |     | —          | —            |            | 0.12       | 0.013      |
| —  | —   | 0.16       | 0.016        |            | 0.011      | BSS0.5-30  |
| M3 | 3.5 |            |              |            | 0.010      | BSS0.5-30A |
| M3 | 3.5 |            |              |            | 0.0099     | BSS0.5-30B |
| M4 | 3.5 |            |              |            | 0.0092     | BSS0.5-30C |
| M3 | 3.5 | 0.22       | 0.022        |            | 0.018      | BSS0.5-38A |
| —  | —   | 0.23       | 0.024        |            | 0.020      | BSS0.5-40  |
| M3 | 3.5 | 0.31       | 0.031        |            | 0.033      | BSS0.5-50A |
| —  | —   | 0.31       | 0.032        |            | 0.014      | BSS0.8-20  |
| M4 | 4   | 0.40       | 0.041        |            | 0.021      | BSS0.8-24B |
| —  | —   | 0.43       | 0.043        | 0.024      | BSS0.8-25  |            |
| —  | —   | 0.55       | 0.056        | 0.034      | BSS0.8-30  |            |
| M3 | 4   |            |              | 0.035      | BSS0.8-30A |            |
| —  | —   | 0.79       | 0.081        | 0.046      | BSS0.8-40  |            |
| M4 | 4   | 0.52       | 0.053        | 0.015      | BSS1-16B   |            |
| M4 |     | 0.62       | 0.063        | 0.021      | BSS1-18B   |            |
| M4 |     | 0.73       | 0.074        | 0.026      | BSS1-20C   |            |
| M4 |     | 1.28       | 0.13         | 0.065      | BSS1-30B   |            |
| M4 |     | 1.86       | 0.19         | 0.10       | BSS1-40A   |            |

直齿轮

斜齿轮

内齿轮

齿条

& C  
小齿轮

等径锥齿轮

锥齿轮

交错轴斜齿轮

蜗轮蜗杆

齿轮箱

其他产品

直齿轮

斜齿轮

内齿轮

齿条

& C  
小齿轮

等径锥齿轮

锥齿轮

交错轴斜齿轮

蜗轮蜗杆

齿轮箱

其他产品